

Form for:

**OBJECTION TO A REQUEST FOR TARIFF SUSPENSION/TARIFF QUOTA**

(delete inappropriate measure)

(TURKEY)

**Part I**

Request No:

CN-Code:

Goods description:

Working No:

- Goods are currently produced in the Union or Turkey and are available on the market.
- Equivalent or substitute products are currently obtainable within the Union or Turkey.

Explanatory comments (differences, why and how it may replace the requested product):

Technical data sheets which prove the character and quality of the offered product have to be attached.

- Other:

Suggested compromise (explanatory comments):

Transfer into a tariff quota:

Suggested quota volume:

Partial tariff suspension:

Suggested duty rate:

Other proposals:

Remarks:

**Company producing currently an identical, equivalent or substitute product  
within the EU or Turkey**

Name of the company:

Person to contact:

Address:

Tel.:

Fax:

E-mail:

Product trade name:

OBJECTION TO A REQUEST FOR TARIFF SUSPENSION/TARIFF QUOTA

(delete inappropriate measure)

(TURKEY )

Part II

Production capacity (available for the market; e.g. not bound in house or by contracts):

Present:

Within the next six months:

\_\_\_\_\_

1/7/2017 Dönemi İçin Askıya Alma veya Tarife Kontenjanı Başvurusu Yapılmış Ürünler

| CN code       | TAXUD  | Product description   | S/Q         |
|---------------|--|---|-------------|
| 2519901010    | 254871/<br>2011  | <i>Current wording:</i><br>Fused magnesia with a purity by weight of 97% or more<br><br><i>Proposed new wording:</i><br>Fused magnesia with a purity by weight of 94% or more   | S           |
| 27122090      | 5503430/2016<br>5503608/2016<br>5459963/2016<br>5503506/2016<br>5503114/2016 | Paraffin wax containing by weight less than 0,75% of oil  | Q           |
| 28257000      | 5559884/2016   | Molybdic Acid (CAS RN 7782-91-4)  | S           |
| 2905110010    | 3090865/2013   | <i>Current wording:</i><br>Methanol (CAS RN 67-56-1) with a purity by weight of 97% or more<br><br><i>Proposed new wording:</i><br>Methanol (CAS RN 67-56-1) with a purity by weight of 99,85% or more (as determined by the Methanol purity method IMPCA 001-14) | S           |
| 29052200      | 5450710/2016   | 3,7-dimethyloct-6-en-1-ol (CAS RN 106-22-9)   | S           |
| 29053100      | 5555215/2016   | Ethylene glycol (Ethandiol)   | Q/21<br>4kT |
| 29053995 (20) | 5501275/2016   | Butane-1,2-diol (CAS RN 584-03-2)   | S           |
| 29091990      | 5531326/2016   | (((2,2-dimethylbut-3-yn-1-yl)oxy)methyl)benzene (CAS RN 1092536-54-3)   | S           |
| 29093090      | 5450733/2016   | 1,2-diphenoxyethane (CAS RN 104-66-5)   | S           |
| 2909600020    | 329376/<br>2011  | <i>Current wording</i><br>1,4-Di(2- <i>tert</i> -butylperoxyisopropyl)benzene (CAS RN 25155-25-3)<br><br><i>Proposed new wording:</i>   | S           |

| CN code  | TAXUD  | Product description   | S/Q              |
|----------|--|---|------------------|
|          |  | 1,4-Di(2-tert-butylperoxyisopropyl)benzene (CAS RN 2781-00-2) or mixture of isomers 1,4-Di(2-tert-butylperoxyisopropyl)benzene and 1,3-di(2-tert-butylperoxyisopropyl)benzene (CAS RN 25155-25-3) |                  |
| 29121900 | 5450756/2016   | Undecanal (CAS RN 112-44-7)   | S                |
| 29153100 | 5582741/2016   | Ethyl acetate (CAS RN 141-78-6)   | Q/<br>1084<br>9T |
| 29153200 | 726215/ 2014<br>825537/ 2014<br>838627/ 2014<br>838774/ 2014<br>898981/ 2014 | Vinyl acetate   | Q/22<br>5kT      |
| 29161200 | 5460155/2016   | Oxybis(methyl-2,1-ethanediyl) diacrylate (CAS RN 57472-68-1)  | S                |
| 29161200 | 5459999/2016   | 2-Acryloyloxymethyl-2-ethyltrimethylene diacrylate (CAS RN: 15625-89-5)   | S                |
| 29161200 | 5460042/2016   | Hexamethylene diacrylate (CAS RN 13048-33-4)  | S                |
| 29163990 | 5552271/2016   | Methyl 4'-(bromomethyl)biphenyl-2-carboxylate (CAS RN 114772-38-2)  | S                |
| 29172000 | 5654291/2016   | 1,2-Cyclohexanedicarboxylic acid, 1-butyl 2-(phenylmethyl) ester (CAS RN 1200806-67-2)  | S                |
| 29189990 | 5450776/2016   | (2,4-Dichlorophenyl)acetyl chloride (CAS RN 53056-20-5)   | S                |
| 29199000 | 5652420/2016   | Isodecyl diphenyl phosphate (CAS RN 29761-21-5)   | S                |
| 29221985 | 5531479/2016   | (R)-1-((4-amino-2-bromo-5-fluorophenyl)amino)-3-(benzyloxy)propan-2-ol 4-methylbenzenesulfonate (CAS RN 1294504-64-5)   | S                |
| 29242998 | 5450799/2016   | Sodium 4-(4-methyl-3-nitrobenzoylamino)benzenesulphonate (CAS RN 84029-45-8)  | S                |
| 29242998 | 5227004/2016   | N-Benzyloxycarbonyl-l-tert-leucina isopropylamine salt (CAS RN 1621085-33-3)  | S                |
| 29269095 | 5572875/2016   | 4,5-dichloro-3,6-dioxocyclohexa-1,4-diene-1,2-dicarbonitrile (CAS RN 84-58-2)   | S                |
| 29309099 | 5573326/2016   | Mixture of isomers of 1-(tert-dodecylthio)propan-2-ol (CAS RN 67124-09-8)   | S                |
| 29321200 | 5457221/2016   | 2-Furaldehyde (CAS RN 98-01-1)  | Q/1<br>0kT       |
| 29329900 | 5572888/2016   | (4-chloro-3-(4-ethoxybenzyl)phenyl)((3aS,5R,6S,6aS)-6-hydroxy-2,2-dimethyltetrahydrofuro[2,3-d][1,3]dioxol-5-yl)methanone (CAS RN 1103738-30-2)   | S                |
| 29329900 | 5531421/2016   | 4-(4-bromo-3-((tetrahydro-2H-pyran-2-yloxy)methyl)phenoxy)benzonitrile (CAS RN 943311-78-2)   | S                |

| CN code    | TAXUD        | Product description   | S/Q |
|------------|--------------|---|-----|
| 29331990   | 5552079/2016 | 5-methyl-1-(naphthalen-2-yl)-1H-pyrazol-3-ol (CAS RN 1192140-15-0)  | S   |
| 29331990   | 5450826/2016 | 5-Amino-1-[2,6-dichloro-4-(trifluoromethyl)phenyl]-1H-pyrazole-3-carbonitrile (CAS RN 120068-79-3)  | S   |
| 29332990   | 5450845/2016 | 2,2'-Azobis[2-(2-imidazolin-2-yl)propane] dihydrochloride (CAS RN 27776-21-2)   | S   |
| 29333999   | 5552155/2016 | 2-chloro-6-(3-fluoro-5-isobutoxyphenyl)nicotinic acid   | S   |
| 29333999   | 5450881/2016 | Fluopicolide (ISO) (CAS RN 239110-15-7)   | S   |
| 29333999   | 5552032/2016 | 5-(3-chlorophenyl)-3-methoxypyridine-2-carbonitrile (CAS RN 1415226-39-9)   | S   |
| 29333999   | 5552224/2016 | 2-aminopyridin-4-ol hydrochloride (CAS RN 1187932-09-7)   | S   |
| 29339980   | 5531366/2016 | (2S,3S,4R)-methyl 3-ethyl-4-hydroxypyrrolidine-2-carboxylate 4-methylbenzenesulfonate (CAS RN 1799733-43-9)   | S   |
| 29339980   | 5450905/2016 | Tivantinib (INN) (CAS RN 905854-02-6)   | S   |
| 29339980   | 5531531/2016 | 3-chloro-2-(1,1-difluorobut-3-enyl)-6-methoxyquinoxaline (CAS RN 1799733-46-2)  | S   |
| 29339980   | 5552188/2016 | (S)-2,2,4-trimethylpyrrolidine hydrochloride  | S   |
| 29349990   | 5552312/2016 | Cytidine 5'-monophosphate disodium salt (CAS RN 6757-06-8)  | S   |
| 29349990   | 5501295/2016 | 4-Methoxy-3-(3-morpholin-4-yl-propoxy)-benzonitrile (CAS RN 675126-28-0), whether or not in organic solvents  | S   |
| 29349990   | 5501233/2016 | 4-Methoxy-5-(3-morpholin-4-yl-propoxy)-2-nitro-benzonitrile (CAS RN 675126-26-8)  | S   |
| 29349990   | 5450922/2016 | Thidiazuron (ISO) (CAS RN 51707-55-2)   | S   |
| 29350090   | 5552111/2016 | 6-aminopyridine-2-sulfonamide (CAS RN 75903-58-1)   | S   |
| 3204160020 | 779822/ 2014 | <p><i>Current wording:</i></p> <p>Colourant Reactive Black 5 (CAS RN 17095-24-8) and preparations based thereon with a colourant Reactive Black 5 content of 60 % or more but not more than 75 % by weight, and including one or more of the following:</p> <ul style="list-style-type: none"> <li>• Colourant Reactive Yellow 201 (CAS RN 27624-67-5),</li> <li>• 1-Naphthalenesulphonicacid,4-amino-3-[[4-[[2-(sulphooxy)ethyl]sulphonyl]phenyl]azo]-, disodium salt (CAS RN 250688-43-8), or</li> <li>• 3,5-diamino-4-[[4-[[2-(sulphooxy)ethyl]sulphonyl]fenyl]azo]-2-[[2-sulfo-4-[[2-(sulphooxy)ethyl]sulfonyl]phenyl]azobenzoic acid sodium salt (CAS RN 906532-68-1)</li> </ul> | S   |

| CN code      | TAXUD        | Product description  | S/Q |
|--------------|--------------|--|-----|
|              |              | <p><i>Proposed new wording:</i><br/> Preparations based on colorant reactive black 5 (CAS RN 17095-24-8) containing 60 % or more by weight of this colorant, whether including or not, one or more of the following:</p> <ul style="list-style-type: none"> <li>• Colorant Reactive Yellow 201 (CAS RN 27624-67-5),</li> <li>• 1-Naphthalenesulphonicacid,4-amino-3-[[4-[[2-(sulphooxy)ethyl]sulphonyl]phenyl]azo]-, disodium salt (CAS RN 250688-43-8), or</li> <li>• 3,5-diamino-4-[[4-[[2-(sulphooxy)ethyl]sulphonyl]phenyl]azo]-2-[[2-sulfo-4-[[2-(sulphooxy)ethyl]sulfonyl]phenyl]azobenzoic acid sodium salt (CAS RN 906532-68-1)</li> </ul> |     |
| 32041700(55) | 5582590/2016 | Colourant C.I. Pigment Red 169 (CAS RN 12237-63-7) and preparations based thereon with a Colourant C.I. Pigment Red 169 content of 50% or more by weight   | S   |
| 32041700(67) | 5582640/2016 | Colourant C.I. Pigment Red 57:1 (CAS RN 5281-04-9) and preparations based thereon with a Colourant C.I. Pigment Red 57:1 content of 50% or more by weight  | S   |
| 38112100     | 5573295/2016 | Dispersing agent and oxidation inhibitor containing : <ul style="list-style-type: none"> <li>• o-amino polyisobutylene phenol (CAS RN 78330-13-9),</li> <li>• more than 30% by weight but not more than 50% by weight of mineral oils, used in the manufacture of blends of additives for lubricating oils (1)</li> </ul>  | S   |
| 38112100     | 5572847/2016 | Detergent containing: <ul style="list-style-type: none"> <li>• calcium long chain alkyltoluenesulphonates,</li> <li>• calcium borate and</li> <li>• more than 10% but not more than 40% by weight of mineral oils, used in the manufacture of blends of additives for lubricating oils (1)</li> </ul>  | S   |
| 38112100     | 5573482/2016 | Detergent containing : <ul style="list-style-type: none"> <li>• a magnesium salt of tetrapropylphenol and formaldehyde polymer,</li> <li>• more than 40% by weight but not more of 60% by weight of mineral oil,</li> <li>• having a total base number of more than 40 but not more than 100, for use in the manufacture of blends of additives for lubricating oils (1)</li> </ul>  | S   |
| 3811210057   | 827236/ 2014 | <p><i>Current wording:</i><br/> Additives containing:</p>  | S   |

| CN code  | TAXUD        | Product description   | S/Q |
|----------|--------------|---|-----|
|          |              | <ul style="list-style-type: none"> <li>a polyisobutylene succinimide based mixture, and</li> <li>more than 40 % but not more than 50 % by weight of mineral oils, having a total base number of more than 40, for use in the manufacture of lubricating oils</li> </ul> <p><i>Proposed new wording:</i><br/>Additives containing:</p> <ul style="list-style-type: none"> <li>a polyisobutylene succinimide based mixture, and</li> <li>more than 30 % but not more than 50 % by weight of mineral oils, having a total base number of more than 40, for use in the manufacture of lubricating oils</li> </ul> |     |
| 38119000 | 5572943/2016 | Corrosion inhibitor containing : <ul style="list-style-type: none"> <li>polyisobutenyl succinic acid and</li> <li>more than 5% and not more than 20% by weight of mineral oils.</li> </ul> used in the manufacture of blends of additives for fuels (1)   | S   |
| 38122090 | 5654225/2016 | 1,2-benzenedicarboxylic acid, benzyl C7-9-branched and linear alkyl esters (CAS RN 68515-40-2)  | S   |
| 38249092 | 5460118/2016 | Poly[oxy(methyl-1,2-ethanediyl)], $\alpha, \alpha', \alpha''$ -1,2,3-propanetriyltris[ $\omega$ -[(1-oxo-2-propen-1-yl)oxy]- (CAS RN 52408-84-1)  | S   |
| 38249092 | 5460258/2016 | Poly(oxy-1,2-ethanediyl), $\alpha$ -hydro- $\omega$ -[(1-oxo-2-propenyl)oxy]-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol, reaction product with 2-amino-ethanol (CAS RN 188012-57-9)   | S   |
| 38249092 | 5582909/2016 | Aqueous solution of caesium formate and potassium formate containing by weight: <ul style="list-style-type: none"> <li>1% or more but not more than 84% of caesium formate (CAS RN 3495-36-1), and</li> <li>1% or more but not more than 75% of potassium formate (CAS RN 590-29-4)</li> </ul> with a density range of 1.57 sg or more but not more than 2.2 sg   | S   |
| 38249092 | 5651680/2016 | Aqueous solution of caesium formate containing by weight 60% or more but not more than 84% of caesium formate   | S   |
| 38249092 | 5651724/2016 | Aqueous solution of caesium formate and potassium formate containing by weight: <ul style="list-style-type: none"> <li>1% or more but not more than 84% of caesium formate (CAS RN 3495-36-1), and</li> <li>1% or more but not more than 76% of potassium formate (CAS RN 590-24-1)</li> </ul>  | S   |
| 38249092 | 5654333/2016 | Preparation containing by weight:   | S   |

| CN code  | TAXUD        | Product description   | S/Q       |
|----------|--------------|---|-----------|
|          |              | <ul style="list-style-type: none"> <li>• 25% or more but not more than of diethyl carbonate (CAS RN 105-58-8)</li> <li>• 25% or more but not more than 50% of ethylene carbonate (CAS RN 96-49-1)</li> <li>• 10% or more but not more than 20% of lithium hexafluorophosphate (CAS RN 21324-40-3)</li> <li>• 5% or more but not more than 10% of ethyl methyl carbonate (CAS RN 623-53-0)</li> <li>• 1% or more but not more than 2% of vinylene carbonate (CAS RN 872-36-6)</li> <li>• 1% or more but not more than 2% of 4-fluoro-1,3-dioxolane-2-one (CAS RN 114435-02-8)</li> <li>• Not more than 1% of 1,5,2,4-Dioxadithiane 2,2,4,4-tetraoxide (CAS RN 99591-74-9)</li> </ul> |           |
| 38249092 | 5573365/2016 | Mixtures containing : <ul style="list-style-type: none"> <li>• 60 % or more but not more than 90 % by weight of 2-chloropropene (CAS RN 557-98-2),</li> <li>• 8 % or more but not more than 14 % by weight of (Z)-1-chloropropene (CAS RN 16136-84-8),</li> <li>• 5 % or more but not more than 23 % by weight of 2-chloropropane (CAS RN 75-29-6),</li> <li>• not more than 6 % by weight of 3-chloropropene (CAS RN 107-05-1) and,</li> <li>• not more than 1 % by weight of ethyl chloride (CAS RN 75-00-3)</li> </ul>   | Q/3<br>kT |
| 38249093 | 5505061/2016 | Sodium hydrogen 3-aminonaphthalene-1,5-disulfonate containing by weight: <ul style="list-style-type: none"> <li>• not more than 20 % of disodium sulphate, and</li> <li>• not more than 10 % of sodium chloride</li> </ul>  | S         |
| 38249096 | 5501338/2016 | Mixture consisting of <ul style="list-style-type: none"> <li>• 64 % or more, but not more than 74 % by weight of by weight of amorphous silica(CAS RN 7631-86-9)</li> <li>• 25 % or more, but not more than 35 % by weight of butanone (CAS RN 78-93-3) and</li> <li>• not more than 1 % by weight of 3-(2,3-epoxypropoxy)propyltrimethoxysilane (CAS RN 2530-83-8)</li> </ul>  | S         |
| 38249096 | 1268378      | Mixture with a non-stoichiometric composition: <ul style="list-style-type: none"> <li>• with a crystalline structure,</li> <li>• with a dominating participation of magnesia-alumina spinel and with admixtures of</li> </ul>   | S         |



| CN code    | TAXUD        | Product description  | S/Q |
|------------|--------------|--|-----|
|            |              | <p>silicate phases and aluminates, at least 75 % by weight of which make fractions with a grain size of 1-3 mm and at most 25 % make fractions with a grain size of 0-1 mm</p> <p>Mixture with a non-stoichiometric composition:</p> <ul style="list-style-type: none"> <li>• with a crystalline structure,</li> <li>• with a content of fused magnesia-alumina spinel and with admixtures of silicate phases and aluminates, at least 75 % by weight of which make fractions with a grain size of 1-3 mm and at most 25 % make fractions with a grain size of 0-1 mm</li> </ul> |     |
| 38249096   | 5582818/2016 | <p>Powder containing by weight:</p> <ul style="list-style-type: none"> <li>• 28% or more but not more than 32% of talc</li> <li>• 43% or more but not more than 48% of silicon dioxide (quartz)</li> <li>• 22% or more but not more than 26% of aluminium oxide</li> </ul> <p>[for use in the manufacture of U-type glass fibre]</p>   | S   |
| 38249096   | 5582854/2016 | <p>Powder containing by weight:</p> <ul style="list-style-type: none"> <li>• 46% or more but not more than 51% of talc</li> <li>• 30.5% or more but not more than 34.5% of silicon dioxide (quartz)</li> <li>• 17.5% or more but not more than 20.5% of aluminium oxide</li> </ul> <p>[for use in the manufacture of K-type glass fibre]</p>   | S   |
| 3824999221 | 3675457/2015 | <p><i>Current wording:</i><br/>Solution of 2-chloro-5-(chloromethyl)-pyridine (CAS RN 70258-18-3) in Toluene</p> <p><i>Proposed new wording:</i><br/>Solution of 2-chloro-5-(chloromethyl)-pyridine (CAS RN 70258-18-3) in organic diluent</p>   | S   |
| 3824999224 | 1367671/2016 | <p>Mixture containing two or more of the following acrylates;</p> <ul style="list-style-type: none"> <li>• urethane acrylates</li> <li>• tripropylene glycoldiacrylate,</li> <li>• ethoxylated bisphenol A acrylate or</li> <li>• poly(ethyleneglycol) 400 diacrylate</li> </ul>   | S   |
| 39053000   | 5451094/2016 | With acetoacetate groups modified poly (vinyl alcohol), containing nonhydrolyzed acetyl groups [for the production of thermal paper]   | S   |

| CN code    | TAXUD        | Product description  | S/Q              |
|------------|--------------|--|------------------|
| 39053000   | 137255/2010  | Poly(vinyl alcohol), whether or not containing unhydrolysed acetyl groups  | Q/<br>225<br>00T |
| 39069090   | 5451123/2016 | Copolymer of butyl acrylate, methyl methacrylate and dimethylsiloxane (CAS RN 143106-82-5) [in form of a white powder]   | S                |
| 39069090   | 5457188/2016 | Polyacrylamide powder having an average particle size of less than 2 microns and a melting point of more than 260°C, containing by weight: <ul style="list-style-type: none"> <li>• 15% or more but not more than 25% of polyethylene glycol</li> <li>• [- not more than 2% of methanol]</li> </ul>  | S                |
| 3907400025 | 706680/2014  | Polymer blend of polycarbonate and poly(methyl methacrylate) with a polycarbonate content of not less than 98,5 % by weight, in the form of pellets or granules, with a luminous transmittance of not less than 88,5 %, measured using a test sample with a thickness of 4 mm at a wavelength of $\lambda = 400$ nm (according to ISO 13468-2)   | Q/4<br>00T       |
| 39100000   | 5651897/2016 | Dimethyl Siloxane, Hydroxy-terminated polymer with a viscosity: 38-45 mPa.s (PMX 0930)   | S                |
| 39100000   | 5651745/2016 | Dimethyl Siloxane, Hydroxy-terminated polymer with a viscosity of 2000 mPa.s (SFD 1)   | S                |
| 39100000   | 5652366/2016 | Preparation containing by weight: <ul style="list-style-type: none"> <li>• 55% or more but not more than 65% of Vinyl terminated polydimethylsiloxane (CAS RN 68083-19-2 ),</li> <li>• 30% or more but not more than 40% of Dimethylvinylated and trimethylated silica (CAS RN 68988-89-6 ),</li> <li>• 1% or more but not more than 5% of Silicic acid, Sodium salt, reaction products with Chlorotrimethylsilane and Isopropyl alcohol (CAS RN 68988-56-7 )</li> </ul> | S                |
| 39100000   | 5654370/2016 | Vinyl Terminated Polydimethyl Siloxane with a Newtonian viscosity of 7000-12000 cP (SFD 120)   | S                |
| 3911901910 | 1450/7/1995  | Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene)  | Q/<br>550<br>0T  |
| 3913900092 | 768/2005     | <i>Current wording:</i><br>Protein, chemically modified by carboxylation and/or phthalic acid addition, having a weight average molecular weight ( $M_w$ ) of 100 000 to 300 000   | S                |

| CN code    | TAXUD                           | Product description   | S/Q |
|------------|---------------------------------|---|-----|
|            |                                 | <i>Proposed new wording:</i><br>Protein, chemically or enzymatically modified by carboxylation and/or phthalic acid addition and/or hydrolysis, having a weight average molecular weight (Mw) of less than 350 000  |     |
| 39199000   | 5451151/2016                    | Cleaning film consisting of a polymer layer with incorporated abrasive particles on one substrate, for use in the cleaning process of measuring needles in semiconductor manufacture  | S   |
| 3920202960 | 1154/<br>2008                   | Mono-axial oriented film, of a total thickness of not more than 75 µm, consisting of two or three layers, each layer containing a mixture of polypropylene and polyethylene, with a core layer whether or not containing titanium dioxide, having: <ul style="list-style-type: none"> <li>• a tensile strength in the machine direction of 140 MPa or more but not more than 270 MPa and</li> <li>• a tensile strength in the transverse direction of 20 MPa or more but not more than 40 MPa</li> </ul> as determined by test method ASTM D882/ISO 527-3 | S   |
| 3920202970 | 1176/<br>2009<br>461/7/<br>1999 | Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, with a core layer whether or not containing titanium dioxide, having: <ul style="list-style-type: none"> <li>• a thickness of 55 µm or more but not more than 97 µm</li> <li>• a tensile modulus in the machine direction of 0,30 GPa or more but not more than 1,45 GPa, and</li> <li>• a tensile modulus in the transverse direction of 0,20 GPa or more but not more than 0,70 GPa</li> </ul> | S   |
| 39209959   | 5451174/2016                    | Film of ethylene-tetrafluoroethylene in rolls with a thickness of 50 µm, a melting point of 260 ° C and a specific gravity of 1.75 (based on water at a temperature of 4 ° C determined according to the standard ASTM D792)  | S   |
| 39219060   | 5457200/2016                    | Porous Membrane of polytetrafluorethylene (PTFE) laminated to a polyester spunbonded non-woven cloth with <ul style="list-style-type: none"> <li>• a total thickness of more than 0,05mm but not more than 0,20 mm.</li> <li>• [a water entry pressure between 5 and 200 kPa according to the ISO 811 test</li> </ul>   | S   |

| CN code                  | TAXUD        | Product description   | S/Q              |
|--------------------------|--------------|---|------------------|
|                          |              | method],<br><ul style="list-style-type: none"> <li>[an air permeability of 0,08 cm<sup>3</sup>/cm<sup>2</sup>/s or more according to the ISO 5636-5 test method]</li> </ul>   |                  |
| 39269097                 | 5560026/2016 | Silicon decoupling ring, with an inner diameter of 15,4 mm (+0,0/-0,1), of a kind used in car parking aid sensor systems  | S                |
| 40169957                 | 5524327/2016 | Rubber bumper seal with a silicone coating of a length not more than 1 200 mm and with at least five plastic clips for use in the manufacture of goods of Chapter 87  | S                |
| 40169957                 | 5524428/2016 | Air intake hose for air supply to the combustion part of the engine made at least of: <ul style="list-style-type: none"> <li>one flexible rubber hose;</li> <li>metal clips;</li> <li>whether or not of a resonator</li> </ul> for use in the manufacture of goods of Chapter 87  | S                |
| 55041000                 | 1367832/2016 | Artificial staple fibres of viscose rayon not carded, combed or otherwise processed for spinning  | Q/1<br>48k<br>T  |
| 55051010                 | 5451208/2016 | Waste of synthetic fibres (including noils, yarn waste and garnetted stock) in different lengths of nylon or other polyamides (PA6 und PA66)  | Q/1<br>1kT       |
| 70194000<br>70195200     | 1290020/2016 | Woven fabrics of glass filaments in rolls, weighing 15 g/m <sup>2</sup> or more but not more than 220 g/m <sup>2</sup> : <ul style="list-style-type: none"> <li>of a width of 60 cm or more but not more than 160 cm, and</li> <li>with a thickness of 0,020 mm or more but not more than 0,260 mm</li> </ul> for use in the manufacture of prepregs<br><br>Fibreglass fabric <ul style="list-style-type: none"> <li>E-glass filament</li> <li>(supplied) in rolls of a width of 60.0 cm or more, but not more than 160.0 cm,</li> <li>with a fibreglass fabric thickness of 0.020 mm or more, but not more than 0.260 mm,</li> <li>with a grammage of 15 g/m<sup>2</sup> or more, but not more than 220 g/m<sup>2</sup></li> </ul> | Q/<br>853<br>0km |
| 7410110010<br>8507908060 | 328894/ 2011 | <i>Current wording:</i><br>Roll of laminate foil of graphite and copper, with:  | S                |

| CN code                  | TAXUD        | Product description   | S/Q             |
|--------------------------|--------------|---|-----------------|
| 8545909030               |              | <ul style="list-style-type: none"> <li>a width of 610 mm or more but not more than 620 mm, and</li> <li>a diameter of 690 mm or more but not more than 710 mm,</li> </ul> for use in the manufacture of lithium-ion electric vehicle batteries<br><br><i>Proposed new wording:</i><br>Roll of laminate foil of graphite and copper, with: <ul style="list-style-type: none"> <li>a width of 610 mm or more but not more than 620 mm, and</li> <li>a diameter of 690 mm or more but not more than 710 mm,</li> </ul> for use in the manufacture of lithium-ion electric batteries  |                 |
| 76011010                 | 5555177/2016 | Unwrought aluminium, not alloyed  | Q/<br>385<br>kT |
| 76012020                 | 5555303/2016 | Unwrought aluminium, aluminium alloys - slabs & billets   | Q/<br>130<br>kT |
| 76012080                 | 5555261/2016 | Unwrought aluminium, aluminium alloys - other   | Q<br>100<br>kT  |
| 76060000                 | 5457584/2016 | Exhaust gas recirculation (EGR) valve tube made of aluminium alloy complying with standard EN-1706-AC-47100D  | S               |
| 7607199010<br>8507908080 | 328900/ 2011 | <i>Current wording:</i><br>Sheet in the form of a roll consisting of a laminate of lithium and manganese bonded to aluminium, with: <ul style="list-style-type: none"> <li>a width of 595 mm or more but not more than 605 mm, and</li> <li>a diameter of 690 mm or more but not more than 710 mm,</li> </ul> for use in the manufacture of cathodes for lithium-ion electric vehicle batteries<br><br><i>Proposed new wording:</i><br>Sheet in the form of a roll consisting of a laminate of lithium and manganese bonded to aluminium, with: <ul style="list-style-type: none"> <li>a width of 595 mm or more but not more than 605 mm, and</li> </ul> | S               |

| CN code              | TAXUD        | Product description  | S/Q                    |
|----------------------|--------------|--|------------------------|
|                      |              | <ul style="list-style-type: none"> <li>a diameter of 690 mm or more but not more than 710 mm, for use in the manufacture of cathodes for lithium-ion electric batteries</li> </ul>   |                        |
| 76169910             | 5457613/2016 | Exhaust gas recirculation (EGR) valve housing made of aluminium alloy complying with standard EN-1706-AC-44300D or EN-1706-AC-47100D   | S                      |
| 8108905025           | 982750/ 2011 | <p><i>Current wording:</i><br/>Strip of aluminium alloy</p> <p><i>Proposed new wording:</i><br/>Plates, sheets and strip of an alloy of titanium</p>   | S                      |
| 8302490091           | 912/2/ 2004  | Aluminium telescopic handle for use in the manufacture of luggage  | Q/1<br>M<br>piec<br>es |
| 84073320<br>84073380 | 1272671/2016 | <p>Single cylinder, four stroke internal combustion engine with a cylinder capacity of more than 325 cm<sup>3</sup> but not more than 570 cm<sup>3</sup>,</p> <ul style="list-style-type: none"> <li>with overall dimensions of not more than: 320 mm (length) x 381 mm (width) x 550 mm (height),</li> <li>a power of more than 22kW but not more than 35kW,</li> <li>equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (+/- 1 degree)</li> </ul> <p>for use in the manufacture of all-terrain vehicles (ATV) and utility task vehicles (UTV – side by side)</p> <p>Single cylinder, four stroke internal combustion engine with a cylinder capacity of more than 325 cm<sup>3</sup> but not more than 570 cm<sup>3</sup>,</p> <ul style="list-style-type: none"> <li>with overall dimensions of not more than: 320 mm (length) x 381 mm (width) x 550 mm (height),</li> <li>a power of more than 22kW but not more than 35kW,</li> <li>equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (+/- 1 degree)</li> </ul> | S                      |

| CN code                                | TAXUD        | Product description   | S/Q |
|--|--------------|---|-----|
| 84073380<br>84073410<br>84073491       | 1272702/2016 | <p>Single cylinder, four stroke internal combustion engine with a cylinder capacity of more than 850 cm<sup>3</sup> but not more than 1200 cm<sup>3</sup>,</p> <ul style="list-style-type: none"> <li>with overall dimensions of not more than: 350 mm (length) x 480 mm (width) x 560 mm (height),</li> <li>a power of more than 44kW but not more than 130kW,</li> <li>equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (+/- 1 degree)</li> </ul> <p>for use in the manufacture of all-terrain vehicles (ATV) and utility task vehicles (UTV – side by side)</p> <p>Dual cylinder, four stroke internal combustion engine with a cylinder capacity of more than 850 cm<sup>3</sup> but not more than 1200 cm<sup>3</sup>,</p> <ul style="list-style-type: none"> <li>with overall dimensions of not more than: 350 mm (length) x 480 mm (width) x 560 mm (height),</li> <li>a power of more than 44kW but not more than 130kW,</li> <li>equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (+/- 1 degree) or ended with a boss</li> </ul> | S   |
| 8409910065<br>8409990030<br>8411990070 | 371591/ 2013 | <p>Spiral-shaped gas turbine turbocharger component:</p> <ul style="list-style-type: none"> <li>with a heat-resistance of not more than 1 050 °C,</li> <li>with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm,</li> <li>whether or not with an engine exhaust manifold</li> </ul>  | S   |
| 84099900                               | 5506673/2016 | <p>Plastic or aluminum cylinder head cover with</p> <ul style="list-style-type: none"> <li>camshaft position sensor (CMPS),</li> <li>inserts for counterparts assembly whether or not used for mounting wires,</li> <li>metal brackets for mounting to engine,</li> <li>two or more gaskets</li> </ul> <p>for use in the manufacture of engines of motor vehicles</p>   | S   |
| 84099900                               | 5506241/2016 | Fuel hose for internal combustion piston engines with a fuel temperature sensor, with at  | S   |

| CN code    | TAXUD        | Product description  | S/Q                       |
|------------|--------------|--|---------------------------|
|            |              | least two inlet hoses and three outlet hoses for use in the manufacture of engines of motor vehicles   |                           |
| 84133080   | 5506724/2016 | High pressure pump for gasoline direct injection with operating pressure of 200 bar or more, but not more than 350 bar for use in the manufacture of engines of the motor vehicles   | S                         |
| 84149000   | 5572918/2016 | Compressor wheel of a kind use for turbo-compressors in car manufacturing industry or other industrial applications: <ul style="list-style-type: none"> <li>• manufactured from aluminum alloy</li> <li>• with a diameter of 20 millimetres or more, but not more than 130 millimetres</li> <li>• with a weight of 5 grams or more, but not more than 800 grams</li> </ul> | Q/<br>295<br>0k<br>pieces |
| 84818040   | 5506338/2016 | Tyre valve with pressure measurement sensor in plastic housing for use in the manufacture of motor vehicles  | S                         |
| 84818059   | 5505106/2016 | Pressure regulating solenoid valve for incorporation into piston compressors of air conditioning machines of motor vehicles (1)  | S                         |
| 84818059   | 5505076/2016 | Pressure regulating valve for incorporation into piston compressors of air conditioning machines of motor vehicles (1)   | S                         |
| 84821090   | 5572818/2016 | Ball bearing, using steel 102Cr6 : <ul style="list-style-type: none"> <li>• having an outside diameter of 37mm,</li> <li>• having an internal diameter of 25mm,</li> <li>• supporting a maximum radial load of 4390N,</li> <li>• supporting an axial load of 2990N</li> </ul>  | S                         |
| 85821090   | 5528937/2016 | Ball bearings with an external diameter of 35 mm and an internal diameter of 15 mm and with a width of 11 mm. The outer ring has special grooves and the ball bearing contains special grease capable of withstanding a performance test in 30 degrees below zero Celsius. Specially made for the injection of plastic wheels  | S                         |
| 84842000   | 5505154/2016 | Shaft seal for incorporation into rotary compressors of air conditioning machines of motor vehicles (1)  | S                         |
| 8501101020 | 3869594/2016 | <i>Current wording:</i><br>Synchronous motor for a dishwasher with a water flow control mechanism with <ul style="list-style-type: none"> <li>• a length without axle of 24 mm (+/- 0,3),</li> <li>• a diameter of 49,3 mm (+/- 0,3)</li> </ul>  | S                         |



| CN code  | TAXUD        | Product description   | S/Q |
|----------|--------------|---|-----|
|          |              | <ul style="list-style-type: none"> <li>• a rated voltage of 220 V AC or more but not more than 240 V AC,</li> <li>• a rated frequency of 50 Hz or more but not more than 60 Hz</li> <li>• an input power of not more than 4 W,</li> <li>• a rotation speed of 4rpm or more but not more than 4,8rpm</li> <li>• an output torque of not more than 10kgf/cm</li> </ul> <p><i>Proposed new wording:</i></p> <p>Synchronous motor for a dishwasher with a water flow control mechanism with</p> <ul style="list-style-type: none"> <li>• a length without axle of 24 mm (+/- 0,3),</li> <li>• a diameter of 49,3 mm (+/- 0,3),</li> <li>• a rated voltage of 220 V AC or more but not more than 240 V AC,</li> <li>• a rated frequency of 50 Hz or more but not more than 60 Hz,</li> <li>• an input power of not more than 4 W,</li> <li>• a rotation speed of 4 rpm or more but not more than 4,8 rpm</li> <li>• an output torque of not less than 10 kgf/cm</li> </ul> |     |
| 85011099 | 5560070/2016 | <p>DC Motor :</p> <ul style="list-style-type: none"> <li>• with a speed rotation of 7000 rounds/minute (without load),</li> <li>• with a nominal voltage of 12V (+/- 4V),</li> <li>• with a maximum power of 13.78W ( under 3.09A),</li> <li>• with a specified temperature range from -40° to 160° ,</li> <li>• with a gear connection,</li> <li>• with a mechanical attachment interface</li> <li>• with 2 electrical connections,</li> <li>• with a maximum torque of 100N.M</li> </ul>  | S   |
| 85011099 | 5560106/2016 | <p>DC Motor :</p> <ul style="list-style-type: none"> <li>• with a speed rotation of 6500 rounds/minute (without load),</li> <li>• with a nominal voltage of 12V (+/- 4V),</li> <li>• with a maximal power below than 20 Watts,</li> </ul>   | S   |

| CN code    | TAXUD        | Product description   | S/Q |
|------------|--------------|---|-----|
|            |              | <ul style="list-style-type: none"> <li>• with a specified temperature range from -40° to 160°,</li> <li>• with a worm gear drive</li> <li>• with a mechanical attachment interface</li> <li>• with 2 electrical connections</li> <li>• with a maximum torque of 75N.M</li> </ul>  |     |
| 8501109955 | 3893585/2015 | <p><i>Current wording:</i><br/>Electric turbocharger actuator</p> <ul style="list-style-type: none"> <li>• a DC motor with an output of 10W or more but not more than 15W,</li> <li>• an integrated gear mechanism,</li> <li>• a (pulling)force of 250N or more at 160°C elevated ambient temperature,</li> <li>• a (pulling) force of 250N or more in each position of its stroke</li> <li>• an effective stroke of 15mm or more but not more than 20 mm,</li> <li>• with or without an on-board diagnostics interface</li> </ul> <p><i>Proposed new wording:</i><br/>Electric turbocharger actuator</p> <ul style="list-style-type: none"> <li>• a DC motor</li> <li>• an integrated gear mechanism,</li> <li>• a (pulling)force of 200 N or more at a minimum of 140 °C elevated ambient temperature,</li> <li>• a (pulling) force of 250 N or more in each position of its stroke,</li> <li>• an effective stroke of 15 mm or more but not more than 25 mm,</li> <li>• with or without an on-board diagnostics interface</li> </ul> | S   |
| 85045095   | 5505747/2016 | <p>Solenoid coil with:</p> <ul style="list-style-type: none"> <li>• A rated power of more than 10 W but not more than 15 W.</li> <li>• An insulation resistance of 100 M Ohms or more</li> <li>• A DC resistance of not more than 34,8 Ohm (± 10%) at 20°C</li> <li>• A rated current of not more than 1,22A</li> </ul>   | S   |

| CN code    | TAXUD                       | Product description   | S/Q |
|------------|-----------------------------|---|-----|
| 8505110033 | 2520/3/<br>2004<br>873/2005 | <ul style="list-style-type: none"> <li>• A rated voltage of not more than 25V</li> </ul> <p><i>Current wording:</i><br/>Permanent magnets consisting of an alloy of neodymium, iron and boron, either in the shape of a rounded rectangle with</p> <ul style="list-style-type: none"> <li>• a length of not more than 90 mm,</li> <li>• a length of not more than 90 mm,</li> <li>• a width of not more than 90 mm and</li> <li>• a height of not more than 55 mm,</li> </ul> <p>or in the shape of a disc with a diameter of not more than 90mm, whether or not containing a hole in the centre</p> <p><i>Proposed new wording:</i><br/>Permanent magnets consisting of an alloy of neodymium, iron and boron, either in the shape of a rectangle, whether or not rounded, with a rectangular or a trapezoidal section having</p> <ul style="list-style-type: none"> <li>• a length of not more than 140 mm,</li> <li>• a width of not more than 90 mm and</li> <li>• a thickness of not more than 55 mm,</li> </ul> <p>or in the shape of curved rectangle (tile type) having</p> <ul style="list-style-type: none"> <li>• a length of not more than 75 mm,</li> <li>• a width of not more than 40 mm,</li> <li>• a thickness of not more than 7 mm and</li> <li>• a radius of curvature of more than 86 mm but not more than 241 m</li> </ul> <p>or in the shape of a disc with a diameter of not more than 90 mm, whether or not containing a hole in the centre.</p> | S   |
| 8505110045 | 816924/ 2015                | <p><i>Current wording:</i><br/>A quarter sleeve, intended to become permanent magnet after magnetisation,</p> <ul style="list-style-type: none"> <li>• consisting of at least neodymium, praseodym, iron, boron, dysprosium, aluminium and cobalt,</li> </ul>   | S   |

| CN code    | TAXUD           | Product description  | S/Q |
|------------|-----------------|--|-----|
|            |                 | <ul style="list-style-type: none"> <li>• with a width of 9,2 mm (- 0,1</li> <li>• with a length of 20 mm (+0,1) or 30 mm (+ 0,1)</li> </ul> of a kind used on rotors for the manufacture of fuel pumps<br><br><i>Proposed new wording:</i><br>A quarter sleeve intended to become permanent magnet after magnetization, <ul style="list-style-type: none"> <li>• consisting of at least neodymium, iron and boron,</li> <li>• with a width of 9,1 mm or more but not more than 10,5 mm,</li> <li>• with a length of 20 mm or more but not more than 30,1 mm,</li> </ul> of a kind used on rotors for the manufacture of fuel pumps.  |     |
| 8505110050 | 312921/<br>2012 | <i>Current wording:</i><br>Bars specifically shaped, intended to become permanent magnets after magnetisation, containing neodymium, iron and boron, with dimensions: <ul style="list-style-type: none"> <li>• a length of 15 mm or more but not more than 52 mm,</li> <li>• a width of 5 mm or more but not more than 42 mm,</li> </ul> of a kind to be used in the manufacture of electric servomotors for industrial automation<br><br><i>Proposed new wording:</i><br>A quarter sleeve, or a quarter sleeve with chamfered longitudinal edges, intended to become permanent magnets after magnetization, <ul style="list-style-type: none"> <li>• consisting of at least neodymium, holmium, dysprosium, boron and iron,</li> <li>• with a width of 10,4 mm (+/- 0,1 mm) or 9,2 mm (- 0,1 mm),</li> <li>• with a length of 20 mm (+ 0,1 mm) or 30 mm (+ 0,1 mm)</li> </ul> of a kind to be used in the manufacture of fuel pumps | S   |
| 8507908070 | 328918/<br>2011 | <i>Current wording:</i><br>Cut plate of nickel-plated copper foil, with: <ul style="list-style-type: none"> <li>• a width of 70 mm (<math>\pm</math> 5 mm),</li> <li>• a thickness of 0,4 mm (<math>\pm</math> 0,2 mm),</li> <li>• a length of not more than 55 mm,</li> </ul>   | S   |

| CN code    | TAXUD        | Product description  | S/Q |
|------------|--------------|--|-----|
|            |              | for use in the manufacture of lithium-ion electric vehicle batteries<br><br><i>Proposed new wording:</i><br>Cut plate of nickel-plated copper foil, with: <ul style="list-style-type: none"> <li>• a width of 70 mm (<math>\pm</math> 5 mm),</li> <li>• a thickness of 0,4 mm (<math>\pm</math> 0,2 mm),</li> <li>• a length of not more than 55 mm,</li> </ul> for use in the manufacture of lithium-ion electric batteries   |     |
| 85184080   | 5523922/2016 | Audio power amplifier in a metal housing with <ul style="list-style-type: none"> <li>- 50 W of power,</li> <li>- a power supply of more than 9 V but not more than 16 V,</li> <li>- an electrical impedance not more than 4 Ohm,</li> <li>- a sensitivity more than 80 dB</li> </ul> for use in the manufacture of motor vehicles  | S   |
| 8522908030 | 277185/ 2011 | <i>Current wording:</i><br>Holder, fixing item or internal stiffener of metal, for use in the manufacture of televisions, monitors and video players<br><br><i>Proposed new wording:</i><br>Metal holder, metal fixing item or internal stiffener of metal, for use in the manufacture of televisions, monitors and video players  | S   |
| 8529909236 | 1093297/2015 | <i>Current wording:</i><br>LCD module with: <ul style="list-style-type: none"> <li>• a diagonal measurement of the screen of 14,5 cm or more but not more than 20,3 cm,</li> <li>• or without a touch screen,</li> <li>• an LED backlight,</li> <li>• a printed circuit board with EEPROM, microcontroller, LVDS receiver and other active and passive components,</li> <li>• a 12 pin <i>plug</i> for power supply and CAN and LVDS interfaces,</li> <li>• in a housing with monitor and other control functions,</li> </ul> for installation in motor vehicles of chapter 87 |     |

| CN code    | TAXUD           | Product description   | S/Q |
|------------|-----------------|---|-----|
|            |                 | <p><i>Proposed new wording:</i><br/>LCD module</p> <ul style="list-style-type: none"> <li>• with a diagonal measurement of the screen of 14,5 cm or more but not more than 38,5 cm,</li> <li>• straight or curved,</li> <li>• with or without a touch screen,</li> <li>• with an LED backlight,</li> <li>• with a printed circuit board with EEPROM, microcontroller, LVDS receiver and other active and passive components,</li> <li>• with a 12 pin plug for power supply and CAN and LVDS interfaces,</li> <li>• with or without electronic components for dynamic adjustments of colour,</li> <li>• in a housing, with or without mechanical, touch-sensitive or contactless control functions and with or without active cooling system,</li> </ul> <p>suitable for installation in motor vehicles of chapter 87</p>   |     |
| 8529909250 | 605694/<br>2010 | <p><i>Current wording:</i><br/>Colour LCD display panel for LCD monitors of heading 8528:</p> <ul style="list-style-type: none"> <li>• with a diagonal measurement of the screen of 14,48 cm or more but not more than 31,24 cm,</li> <li>• with backlight, micro-controller,</li> <li>• with a CAN (Controller area network)-controller with LVDS (Low-voltage differential signalling) interface and CAN/power supply socket or with an APIX (Automotive Pixel Link) controller with APIX interface,</li> <li>• in a housing with or without a heat sink at the back of the housing,</li> <li>• without a signal-processing module,</li> </ul> <p>for use in the manufacture of vehicles of chapter 87</p> <p><i>Proposed new wording:</i><br/>Colour LCD display panel for LCD monitors of heading 8528:</p> <ul style="list-style-type: none"> <li>• straight or curved,</li> </ul> | S   |

| CN code  | TAXUD        | Product description  | S/Q |
|----------|--------------|--|-----|
|          |              | <ul style="list-style-type: none"> <li>• with a diagonal measurement of the screen of 14,48 cm or more but not more than 31,24 cm,</li> <li>• with or without touch screen,</li> <li>• with backlight, micro-controller,</li> <li>• with a CAN (Controller area network)-controller with one or more LVDS (Low-voltage differential signalling) interfaces and one or more CAN/power supply sockets or with an APIX (Automotive Pixel Link) controller with APIX interface,</li> <li>• in a housing with or without a heat sink at the back of the housing,</li> <li>• without a signal-processing module,</li> <li>• whether or not with haptic and acoustical feedback,</li> </ul> <p>for use in the manufacture of vehicles of chapter 87</p> |     |
| 85371099 | 5524531/2016 | Electronic immobilizer control unit with operating voltage of 9V or more, but not more than 16V, in a plastic housing, with a connector, whether or not with metal holder for use in the manufacture of goods of Chapter 87  | S   |
| 85371099 | 5559923/2016 | <p>Lever :</p> <ul style="list-style-type: none"> <li>• with one or more single or multi-positional electrical switches (push-button, rotary or other),</li> <li>• whether or not equipped with printed circuit boards and electrical cables,</li> <li>• for a voltage of 9 V or more but not more than 16 V,</li> <li>• for control module under the steering wheel, mounted on the steering column of motor vehicles of Chapter 87</li> </ul>  | S   |
| 85371099 | 5524483/2016 | <p>Control unit for keyless access and vehicle starting in plastic housing whether or not with:</p> <ul style="list-style-type: none"> <li>• an antenna,</li> <li>• a connector,</li> <li>• a metal holder</li> </ul> <p>for use in the manufacture of goods of Chapter 87</p>   | S   |
| 85389099 | 5559994/2016 | Front control panel, in the form of a plastic box, with light guides, rotary switches, pressure switches and buttons switches, or other type of switches, of a kind used in the dashboard of motor vehicles of Chapter 87  | S   |

| CN code    | TAXUD        | Product description   | S/Q |
|------------|--------------|---|-----|
| 85437090   | 5451360/2016 | Electrochrome film; Made of laminated film with two outer layers of polyester and polyester. An intermediate layer of acrylic polymer and silicone, as well as two electrical layers<br>Connection terminals  | S   |
| 8544200020 | 1233197/2015 | <i>Current wording:</i><br>Antenna connecting cable for the transmission of analogue radio (AM/FM) and GPS signals, containing: <ul style="list-style-type: none"> <li>• a coaxial cable,</li> <li>• two or more connectors,</li> <li>• 3 or more plastic clips for attachment to the dashboard</li> </ul> of kind used in the manufacture of goods of Chapter 87<br><br><i>Proposed new wording:</i><br>Antenna connecting cable for the transmission of analogue radio (AM/FM) and GPS signals, containing: <ul style="list-style-type: none"> <li>• coaxial cable,</li> <li>• two or more connectors,</li> <li>• 3 or more plastic clips for attachment to the dashboard</li> </ul> of kind used in the manufacture of goods of Chapter 87 | S   |
| 85444290   | 5524595/2016 | 12-core connecting cable for voltage of 5V for connecting the control panel to the car radio or navigation, with length of not more than 300 mm and connectors on both ends for use in the manufacture of goods of Chapter 87   | S   |
| 8548909048 | 3117/10/2004 | Optical unit, containing at least <ul style="list-style-type: none"> <li>• a laser diode and a photodiode operating at a typical wavelength of 635 nm or more but not more than 815 nm</li> <li>• an optical lens</li> <li>• a "Recording Photodetector Integrated Circuit" (PDIC)</li> <li>• a focussing and tracking actuator</li> </ul>  | S   |
| 87060091   | 5500085/2016 | Set, containing various parts for a motor vehicle essentially designed to transport not more than six people, including:  | S   |



EK - 3

**EKONOMİ BAKANLIĞI**  
**İthalat Genel Müdürlüğüne**

Avrupa Birliği ile Türkiye arasında ihdas edilen Gümrük Birliği çerçevesinde, .../.../... Dönemi itibariyle gümrük vergilerinin müştereken askıya alınması ve/veya otonom tarife kontenjanı açılması talep edilen ve/veya hâlihazırda İthalat Rejimi Kararı Eki V sayılı listede yer alan ürünlere ilişkin Bakanlığınız resmi internet sitesinde yayımlanan liste kapsamındaki aşağıda belirtilen ürün(ler)de üretimimiz olması gerekçesiyle, söz konusu ürünlerin Askıya Alma Sistemi kapsamına alınmasına itiraz etmekteyiz.

Gereğinin yapılmasını saygılarımla arz ederim.

|                                       |  |
|---------------------------------------|--|
| İtiraz Konusu Ürünün Dosya Numarası   |  |
| İtiraz Konusu Ürünün Tarife Pozisyonu |  |
| Talep Konusu Ürünün Tanımı            |  |

Firma Yetkilisi  
Adı Soyadı, Unvan  
İmza ve Kaşe

**Başvuruya Eklenacak Belgeler:**

- 1) İtiraz Formu (EK - 6)
- 2) Talep konusu ürünün tedarikine ilişkin talep sahibi firma ile üretici (itiraz eden) firma arasındaki görüşmelere dair bilgi ve belgeler
- 3) Geçerli Kapasite Raporu
- 4) Ürüne ilişkin teknik bilgi ve belgeler

EK -6

**ASKIYA ALMAYA / OTONOM TARİFE KONTENJANI AÇILMASINA İLİŞKİN  
İTİRAZ FORMU (Talebe uygun olan seçilir)**

Kısım I

1. Talep No:

2. Tarife Pozisyonu:

3. Talep konusu ürüne ilişkin uygun ürün tanımı:

4. Sıra No:

Ürün(ler) AB ve Türkiye’de hâlihazırda üretilip piyasa arz ediliyor.

Eşdeğer veya ikame ürün(ler) hâlihazırda üretilip piyasa arz ediliyor.

Açıklayıcı bilgi (talep konusu ürünü hangi şekilde ikame edeceği)

Eşdeğer/ikame ürüne ilişkin teknik bilgi/belgeler

Diğer

5. İtirazın içeriği:

Tarife kontenjanına çevrilmesi:

Önerilen tarife kontenjanı miktarı:

Kısmi askıya almaya çevrilmesi:

Önerilen gümrük vergisi oranı:

Diğer:

6. İtiraz konusu ürünün aynısının, eşdeğerinin veya ikamesinin AB veya Türkiye’de yerleşik üreticisi:

Firma Adı:

Firma Yetkilisi:

Adres:

Telefon/Faks:

E-posta:

Ürünün ticari adı:

**ASKIYA ALMAYA / OTONOM TARİFE KONTENJANI AÇILMASINA İLİŞKİN  
İTİRAZ FORMU (Talebe uygun olan seçilir)**

Kısım II

7. Üretim kapasitesi (Piyasa arz edilmeye hazır, sözleşmeye bağlanmamış kapasite):

Mevcut:

Gelecek altı ay içerisinde: